### **Emergency**





#### **OVERVIEW**

Series 512 Surface Pin spot emergency downlight with interchangeable open area and corridor lens to provide flexibility

#### **FEATURES**

- 6500K
- Supplied with interchangeable lenses
- 270lm (open area)
- 230lm (corridor lens)







#### **OPTIONS**

- · Non-Maintained and Self test
- · Round & Square
- · Black & White

T: 01282 476600 | E: info@photoniclighting.co.uk Unit 1 Boran Court, Network 65, Hapton, Burnley BB11 5TH


www.photoniclighting.co.uk

# **SERIES 512**

## **Emergency**





#### **PRODUCT DIMENSIONS**





#### **PHOTOMETRIC**





#### **PRODUCT SPECIFICATION**

512 - 27 - (FN) - (SP) - (CR) - (CCT)

lumen output (LM)	
Code	Description
27	270lm

Housing Colour (CR)	
Code	Description
BK	Black*
WH	White
	*Only NM version

Emergency Function (FN)	
Code	Description
NM	Non-Maintained
SL2	Self test 2W

Correlate	Correlated Colour Temperature (CCT)	
Code	Description	
865	80 CRI 6500K	

Shape (SP)	
Code	Description
RN	Round
SQ	Square

T: 01282 476600 | E: info@photoniclighting.co.uk

Unit 1 Boran Court, Network 65, Hapton, Burnley BB11 5TH

www.photoniclighting.co.uk

# **SERIES 512**

## **Emergency**



#### **OPTIONS**







T: 01282 476600 | E: info@photoniclighting.co.uk Unit 1 Boran Court, Network 65, Hapton, Burnley BB11 5TH

www.photoniclighting.co.uk