Emergency





OVERVIEW

Series 513 is a recessed pin spot luminaire available in self test and manual test, in both Black and White housing colours. The unit comes supplied with both open and corridor lenses which are interchangeable. Separate accessories are available for Surface mounting or expansion rings for larger hole cutouts.

FEATURES

- 1.5W emergency
- 6500K

CE CK Z






OPTIONS

- · Black and White options
- · Surface mount kit available
- Expansion ring

PRODUCT DIMENSIONS



T: 01282 476600 | E: info@photoniclighting.co.uk Unit 1 Boran Court, Network 65, Hapton, Burnley BB11 5TH

www.photoniclighting.co.uk

SERIES 513

Emergency



PHOTOMETRIC

PRODUCT SPECIFICATION

513 - 20 - (FN) - (CR) - (CCT)

lumen output (LM)		
Code	Description	
20	190lm (Corridor)	
	200lm (Open)	


Correlated Colour Temperature (CCT)		
Code	Description	
865	80 CRI 6500K	


Emergency Function (FN)	
Code	Description
M	Manaul test
SL	Self test 1.5W

Housing Colour (CR)		
Code	Description	
BK	Black	
WH	White	

Accessories		
Code	Description	
513-SM-BK	Black surface mount box	
513-SM-WH	White Surface mount box	
513-AR-WH	White expansion ring	

OPTIONS





Expansion ring

Surface mount kit